

Intergrain UltraPrep Timber Cleaner


NZ_DW02693

Part A	55294814
--------	----------

Description
Intergrain UltraPrep™ Timber Cleaner is a high strength timber treatment that contains oxalic acid and citric acid, both naturally occurring, biodegradable acids. Use Intergrain UltraPrep Timber Cleaner to remove surface contaminants prior to coating, the cleaner will help to restore and prepare weathered, grey, rust or tannin stained, mould or mildew affected timber to a clean appearance ready for coating.

Features
<ul style="list-style-type: none"> • High strength concentrate • Contains natural bio-degradable acids

Uses
<p>Prior to coating all exterior timber including decking, outdoor furniture, cladding, screening and fences.</p> <p>Not suitable for interior applications.</p>

Typical Properties	
V.O.C. Level	<10g/L
Clean Up	 Water
Application Method	Other: Stiff bristle brush
Typical Properties Notes	MIX RATIO 1 part UltraPrep Timber Cleaner to 4 parts water COVERAGE Up to 10m ² /L of concentrate

Application Guide	
Surface Preparation	<ul style="list-style-type: none"> • Remove surface dirt by sweeping or washing down with water.
Application Procedure And Equipment	<ul style="list-style-type: none"> • Shake Intergrain UltraPrep Timber Cleaner thoroughly. <p>Mix ONE part Intergrain UltraPrep Timber Cleaner to FOUR parts water in a plastic container. For severely stained surfaces a stronger solution or repeat applications may be necessary. Tannin rich timbers may also require repeat applications; wash until the water used to rinse off is clear.</p> <p>Wet the timber surfaces to be cleaned with water.</p> <p>Apply Intergrain UltraPrep Timber Cleaner mixture generously to the timber with a stiff bristle brush. Scrub the timber vigorously. Spot cleaning should be avoided to prevent patchy results. Leave mixture on the timber for 10-15 minutes. If necessary, apply more mixture to keep timber damp throughout this period, do not allow mixture to dry. Rinse off surface thoroughly using maximum pressure from a garden hose or using a high pressure water cleaner (recommended for large areas or badly discoloured timber). Failure to thoroughly rinse off the mixture may result in timber discolouration under clear finishes.</p> <p>Note: After cleaning, some timber species will appear lighter due to loss of water soluble extractives. Richer colour is generally restored on application of the finish.</p> <p>HELP & ADVICE Australia – 1800 630 285 www.intergrain.com.au NZ – 0800 222 687 www.intergrain.co.nz</p> <p>For detailed project specifications</p>

Health And Safety			
MSDS Number	DLXNZLEN000003	Using Safety Precautions	Keep out of reach of children. Read label before use. Do not breathe dust, fume, gas, mist, vapours or spray. Wash hands, face and all exposed skin thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wear protective clothing, gloves, eye/face protection and suitable respirator.
MSDS Link	https://go.lupinsys.com/duluxgroup/harms/pm/3c8bb9f28239cf735c4e49d35e546b09-published/attachment/nz-sds.pdf		
Health Effects	DANGER May be harmful if swallowed. Causes severe skin burns and eye damage. May cause an allergic skin reaction. Harmful to aquatic life with long lasting effects.	Flammability	Non Flammable
Personal	FIRST AID: If poisoning occurs, contact a Doctor or Poisons Information Centre (New Zealand 0800 764 766; Phone Australia 131 126). If medical advice is needed, have product container or label at hand. SWALLOWED: If swallowed, do NOT induce vomiting. Give a glass of water. Seek medical advice. EYE: If in eyes, hold eyes open, flood with water for at least 15 minutes and see a doctor. SKIN: If skin contact occurs, remove contaminated clothing and wash skin thoroughly. If irritation occurs seek medical advice. INHALED: Remove from contaminated area. Seek medical advice.	Fire Suppression	If material is involved in a fire use water fog (or if unavailable fine water spray), foam, dry agent (carbon dioxide, dry chemical powder).
Protective Equipment	Wear safety shoes, overalls, gloves, chemical goggles. Available information suggests that gloves made from nitrile rubber should be suitable for intermittent contact.	Storage	Keep out of reach of children. Store in a cool, dry, well-ventilated place and out of direct sunlight. Store away from foodstuffs. Store away from oxidising agents.
Other	Contains 1-10% (w/w) Benzalkonium chloride, Oxalic acid dihydrate 1-10% (w/w), and D-limonene <1% (w/w)		
In the case of emergency, please call 0800 734 607			

Precautions And Limitations
Exterior use only. Not suitable for interior use.
Wear waterproof gloves and safety glasses.
Avoid contact with painted, glass, concrete or metal surfaces and vegetation. Protect areas not to be cleaned.
May be corrosive to metals. Rinse off thoroughly if contact occurs.

Transport And Storage			
Pack A	55294814	Shipment Name	CORROSIVE LIQUID, N.O.S. (OXALIC ACID)
Size	Weight		
1L	1.235		
4L	4.367		
UN Number	1760	Dangerous Goods Class	8
Package Group	I		

Disclaimer

Dulux, Selleys and Other marks followed by ® are registered trademarks. Marks followed by the symbol of ™ are trademarks.

The data provided within the Duspec system is correct at the time of publication, however it is the responsibility of those using this information to check that it is current prior to specifying or using any of these coating/product systems.

DISCLAIMER: Any advice, recommendation, information, assistance or service provided by any of the divisions of DuluxGroup (New Zealand) Pty Ltd or its related entities (collectively, DuluxGroup) in relation to goods manufactured by it or their use and application is given in good faith and is believed by DuluxGroup to be appropriate and reliable. However, any advice, recommendation, information, assistance or service provided by DuluxGroup is provided without liability or responsibility PROVIDED THAT the foregoing shall not exclude, limit, restrict or modify the right entitlements and remedies conferred upon any person or the liabilities imposed upon DuluxGroup by any condition or warranty implied by Commonwealth, State or Territory Act or ordinance void or prohibiting such exclusion limitation or modification. Coating/product systems can be expected to perform as indicated on the Duspec Spec Sheet so long as applications and application procedures of the individual products are followed as recommended on the appropriate Product data Sheet. "DuluxGroup" "Dulux" "Selleys" "Berger" "Berger Gold Label" "Hadrian" "Walpamur" "Levene" "Acratex" and Other marks followed by ® are registered trademarks. Marks followed by the symbol ™ are trademarks.

Please note that this document is only valid for 60 days from the date of issue.

DuluxGroup (New Zealand) Pty Ltd 150 Hutt Park Road NZ ACN 133 404 118