

Hydro Flashing Tape is a bituminous flashing tape to seal around windows, doors, and other joinery openings as a secondary defence against water penetration. Adhesion from 5°C.

### Applications

- It's suitable for timber and steel framed buildings
- Simple 4 step installation, save time reducing costs
- Reliable and dependable weather tightness
- Works in temperatures from 5°C
- An *Optional Corner Guard* is easy to install and increases protection to framing

NB. *Masons Hydro Flashing Tape* and *Masons Corner Guard* must be installed in accordance with the instructions outlined on page 11 of this catalogue.

### New Zealand Building Code Standard (NZBC)

- Has been tested and passed by **CodeMark**
- For a risk score between 0-20 in accordance with NZBC Acceptable Solution E2/AS1
- Passed NZS3604 Building Wind Zones up to and including 'Extra High'

### Physical Properties

- **Compatible** with most building wraps

**WARNING: Don't apply any solvent based glues or adhesives/sealants to the tape as it will react with the bitumen.**



Corner Guard

**Note: 150mm Wide tape is used for 100mm wide window or door framing. 200mm wide tape is used for 140mm-150mm wide levels.**

Hydro flashing tape	Roll Sizes	Masons Code
Hydro flashing tape 75mm	H 75mm x L 25m	HYDRO75x25
Hydro flashing tape 100mm	H 100mm x L 25m	HYDRO100x25
Hydro flashing tape 150mm	H 150mm x L 25m	HYDRO150x25
Hydro flashing tape 150mm	H 150mm x L 10m	HYDRO150x10
Hydro flashing tape 200mm	H 200mm x L 25m	HYDRO200x25
Masons corner guards pack of 10	pack of 10	HYDRO10CNRGUARD
Masons corner guards pack of 50	pack of 50	HYDROCG50

