

**MASONS ROOF BOOTS**  
**BUILDING PRODUCT**  
**INFORMATION SHEET**



**MASONS**  
 Designed Smart, Built Tough.

V2.0 February 2024

**PRODUCT NAME**

Masons Roof Boots

**PRODUCT LINE**

Masons Roofing accessories

**PRODUCT DESCRIPTION AND ITS INTENDED USE:**

Masons Roof Boots are exterior flexible flashings for cylindrical penetrations to roof cladding. Roof Boots are comprised of either an EPDM or Silicone rubber cone and flange, with a malleable aluminium perimeter that is moulded to the roof cladding and fixed with fastenings and sealant.

**PRODUCT IDENTIFIERS**

RBFBE 0-20mm	Roof Boot Flashing 0-20mm BLK EPDM	Pipe size: 0-20mm Base size: 57 × 57cm
RBFBE 0-35mm	Roof Boot Flshg 0-35mm Blk EPDM	Pipe size: 0-20mm Base size: 57 × 57cm
RBFBE 110-170mm	Roof Boot Flshg 110-170mm Blk EPDM	Pipe size: 110-170mm Base size: 283 × 283cm
RBFBE 130-230mm	Roof Boot Flshg 130-230mm Blk EPDM	Pipe size: 130-230mm Base size: 305 × 305cm
RBFBE 160-220mm	Roof Boot Flshg 160-220mm Blk EPDM	Pipe size: 160-220mm Base size: 360 × 360cm
RBFBE 160-300mm	Roof Boot Flshg 160-300mm Blk EPDM	Pipe size: 160-300mm Base size: 445 × 445cm
RBFBE 5-120mm	Roof Boot Flshg 5-120mm Blk EPDM	Pipe size: 5-120mm Base size: 215-215cm
RBFBE 5-55mm	Roof Boot Flshg 5-55mm Blk EPDM	Pipe size: 5-55mm Base size: 135-135cm
RBFBE 50-70mm	Roof Boot Flshg 50-70mm Blk EPDM	Pipe size: 50-70mm Base size: 175-175cm
RBFBE CN 0-35mm	Roof Boot Flshg 0-35mm Blk EPDM Cble Nipples	Pipe size: 0-35mm Base size: 92-92cm
RBFBERF 20-70mm	Roof Boot Flshg 20-70mm Blk EPDM Retro Fit	Pipe size: 20-70mm Base size: 160-160cm
RBFRS 0-35mm	Roof Boot Flshg 0-35mm Red Silcn	Pipe size: 0-35mm Base size: 100-100cm
RBFRS 110-170mm	Roof Boot Flshg 110-170mm Red Silcn	Pipe size: 110-170mm Base size: 283-283cm
RBFRS 130-230mm	Roof Boot Flshg 130-230mm Red Silcn	Pipe size: 130-230mm Base size: 305-305cm
RBFRS 160-220mm	Roof Boot Flshg 160-220mm Red Silcn	Pipe size: 160-220mm Base size: 360-360cm
RBFRS 160-300mm	Roof Boot Flshg 160-300mm Red Silcn	Pipe size: 160-300mm Base size: 445-445cm
RBFRS 5-120mm	Roof Boot Flshg 5-120mm Red Silcn	Pipe size: 5-120mm Base size: 215-215cm
RBFRS 50-170mm	Roof Boot Flshg 50-70mm Red Silcn	Pipe size: 50-70mm Base size: 175-175cm
RBFRSCN 0-35mm	Roof Boot Flshg 0-35mm Red Silcn Cble Nipples	Pipe size: 0-35mm Base size: 98-98cm
RBFRSCN 5-55mm	Roof Boot Flshg 5-55mm Red Silcn Cble Nipples	Pipe size: 5-55mm Base size: 137-137cm
RBFRSRF 20-70mm	Roof Boot Flshg 20-70mm Red Silcn Retro Fit	Pipe size: 20-70mm Base size: 153-153cm



---

## PLACE OF MANUFACTURE

China

---

## MANUFACTURER: Legal And Trading Name

Refer to Masons NZ Ltd

---

## IMPORTER: Legal And Trading Name

Company Masons NZ Ltd

Address 18A David McCathie Place, Silverdale, Auckland

Phone number 0800 522 533

Email Address info@mpb.co.nz

Website mpb.co.nz

NZBN 9429031171090

---

## RELEVANT BUILDING CLAUSE

E2 AS1 8.1.7, Table 20, 8.3.10, 8.4.17 Figs 53 & 54

B2 Durability 5 - 15 years - easily accessed / accessed with moderate difficulty exterior materials

F2 Hazardous Materials - no hazardous materials

---

## STATEMENT ON HOW THE PRODUCT IS EXPECTED TO CONTRIBUTE TO COMPLIANCE

Correctly installed Masons Roof Boots contribute to the weather tightness of roof - roof penetrations required under E2/AS1, 8.1.7

---

## LIMITATIONS ON THE USE OF THE PRODUCT

- Do not directly install on roof pitches below 8 Degrees on corrugated profiles and 10 Degrees on low profile trapezoidal profiles.
- When fitted to a correctly sized flat soaker do not install below 10 Degree pitch for corrugated iron and 3 Degree pitch for trapezoidal or trough sections. Roof boots fitted below 8 Degree pitch should not be installed at 45 Degrees to the profile.

---

## INSTALLATION REQUIREMENTS

See Masons Roof Boot Installation requirements, also the MRM COP version 9.5 Boot Flashings.

---

## MAINTENANCE REQUIREMENTS

None.

---

## IS THE BUILDING PRODUCT/BUILDING PRODUCT LINE SUBJECT TO WARNING OR BAN UNDER SECTION 26 OF THE NEW ZEALAND BUILDING CODE?

No.

---