

Air-Flex



MASONS
Designed Smart, Built Tough.

- › A plasticiser manufactured for use by brick and blocklayers.
- › Safe, low dosage and economical.



USES

When using Masons Air-Flex as a mortar additive no additional admixtures are required. The product performs well regardless of the cement and sand types used.

ADVANTAGES

- All types of sand
- Excellent workability
- Longer board life
- User friendly
- Non-toxic
- Cost effective
- Low dosage
- Sturdy plastic container
- Provides good bond strength

APPLICATION

Manual hand mixing:

Thoroughly shake container prior to use

- Dry mix the required sand/cement in a wheel barrow
- Add Masons Air-Flex approx. 10-15g per 20kgs of cement
- Dry mix thoroughly
- Add water to desired consistency and mix
- **Note:** Dosage may vary depending on condition of the sand

Mechanical mixing:

Thoroughly shake container prior to use

- Add two-thirds of the required water to the mixer
- Add 10-20g (1-2 scoops) of Masons Air-Flex
- Add half the required sand and allow to mix
- Add all the cement and the balance of the sand
- Add the balance of the water to obtain the correct consistency



MASONS
Designed Smart, Built Tough.

YIELD

Masons Air-Flex is used at the rate of 30g per 40kg bag of cement. More or less can be used to suit but do not overdose. Usage is dependant on the sand or cement type and condition. If in doubt contact the manufacturer.

Each container of Masons Air-Flex will plasticise the following amount of bags of cement (40kg).

PACKAGING	
Container Size	No of cement bags
0.7kg	23
1.7kg	56
4.0kg	133
10.0kg	333
15.0kg	500

Add Masons Air-Flex approx. 10-15g per 20kg of cement

HEALTH AND SAFETY

- Keep out of reach of children
- May cause skin irritation with repeat contact
- Masons Air-Flex is non toxic, however it should not be swallowed or splashed into eyes. Seek medical advice if this occurs

TECHNICAL SERVICE

For your nearest stockist or additional technical information on Masons products and our wide range of sealing compounds, concrete admixtures and additives for the construction industry, contact Masons on 0800 522 533.

The above information is based on our best knowledge and presented in good faith and we believe it to be true and accurate, however, due to the variable nature of application the suitability of the product for the intended use is the sole responsibility of the user.

Description	Size (kg)	Masons Code
Airflex 700g	700g	AIRFLEX700
Airflex 1.7kg	1.7kg	AIRFLEX1.7
Airflex 4kg	4kg	AIRFLEX4
Airflex 10kg	10kg	AIRFLEX10
Airflex 15kg	15kg	AIRFLEX15