




Aeron® Window Control System Specification Guide

Step 1. Specify Actuators

Specify **one actuator** for window less than 900mm:

A.




Actuators

YAR/WSWA/1/BLK YAR/WSWA/1/P YAR/WSWA/1/SPEC

QTY:

Specify **two actuator** for windows between 900mm and 2400mm

B.



Actuators

YAR/WSWA/1/BLK YAR/WSWA/1/P YAR/WSWA/1/SPEC

QTY

Specify one synchronisation loom for each double actuator installation



Sync Loom YAR/SWAA/SSL

Total number of actuators (A+B):

Total number of synchronisation looms:

Step 2. Specify Power Supply

One power supply can power up to two actuator. For double actuator windows, the same power supply must be used for both actuators



Power Supply

YAR/SWAA/SPS **QTY:**

Step 3. Specify Hub

One Hub can connect up to 30 actuators and 4 remotes



Connect Plus Hub 2

YAR/SWAA/HUB **QTY:**

Step 4. Specify Remote

4 Remotes maximum per system



Remote

YAR/SWAA/ZRT **QTY:**

Step 5. Specify Rain Sensor & Adaptor

Optional. Specify maximum one rain sensor per system



Rain Sensor and Adaptor

YAR/SWAA/SRS **QTY:**