

ARMOURSHIELD GLASS SPECIFICATIONS

Delivering Bent & Specialist Glass with Excellence





glasshape.com



High Risk Intruder Resistant Glass Specifications

Product Code	Description	Thickness	Weight m ²	Attack Rating* (Approx)	AS 3555.1 Level 2 Pass	Light Trans. %	Reflect (out). %	Reflect (in). %	Solar Trans. %	Solar Reflect. %	SC	SHGC	U Value (W/m2K) Summer	U Value (W/m2K) Winter
				SECURITY		LIGHT			SOLAR		THERMAL			
ArmourShield® Clear (optional colour/tints on Custom Products)														
AS14T	Toughened	14.8mm (9/16")	28kg/m²	Up to 5 minutes	PASS 5 minutes	84	7	7	66	6	0.87	0.75	4.33	4.73
AS17T	Toughened	17.9mm (11/16")	34kg/m²	Up to 10 minutes	PASS 10 minutes	83	8	8	60	6	0.83	0.72	4.16	4.54
AS22T	Toughened	22.6mm (7/8")	44kg/m²	Up to 15 minutes	PASS 10 minutes	80	8	8	56	6	0.8	0.69	3.99	4.34
AS26T	Toughened	25.6mm (1")	51kg/m²	Up to 20 minutes	PASS 10 minutes	79	8	8	53	6	0.78	0.68	3.94	4.29

^{*} Attack rating is based on AS3555.1 level 2, attack conditions. Custom options available on all products for tints or additional features or specifications.





Complete certified glass solutions designed for your application

ArmourShield® is specifically designed to provide additional safety for personnel and protect critical areas in buildings, safe houses, detention centres, prisons and marine vessels. ArmourShield® slows down and restricts intruder entry. Even when broken, the tough inner-core of poly-composite will lock the exterior glass layers to enable greater attack resistance. Ideal for doors and windows that maintain the appearance of normal glass, ArmourShield® is specially designed and constructed to remain resistant under attack.

New Zealand

Phone: 0800 883 336 Email: info@glasshape.co.nz **Australia**

Phone: 1800 042 716 Email: info@glasshape.com **United States**

Seattle: New York: Email: +1 206 538 5416 +1 332 255 6319 info@glasshape.com

Version: ARM - 19.2020 glasshape.com