

Mapei Evolight S Roofing & Decking Membrane

Product Technical Statement: 109341

miproducts
THE NATIONAL PRODUCT DATABASE

Evolight S Torch-on Membrane is a SBS modified , polyester reinforced bitumen for roofs and balcony

[View miproducts listing](#)



Level of assurance needed to demonstrate NZ Building Code Compliance

Supporting documentation should include technical information by manufacturer and either a BRANZ or independent Appraisal or CodeMark



Mapei confirms that this minimum level of assurance has been met or exceeded by the following:

BRANZ Appraisal

[1043](#)

Technical Statement

Product Description

Evolight S Torch On membrane is a fully bonded 2 layer , torch on system for use on roofs , gutters , parapets , decks and balconies.

Scope of use

Evolight S Torchon membrane has been BRANZ appraised as a roof and deck waterproofing membrane on buildings within the following scope:

- the scope limitations of NZBC Acceptable solutions E2/AS1 , Paragraph 1.1: or
- the scope of limitations of NZBC Acceptable Solution E2/AS1 Paragraph 1:1 with regards to building height and floor plan area when subject to specific structural design: and,
- with substrates of plywood or suspended concrete slab: and,
- with minimum falls for roofs of 1:30 and decks of 1:40 , and
- with deck size limited to 40m² , and
- situated in NZS 3604 Wind Zones , up to and including Extra high

Roofs and decks waterproofed with Evolight S torch on membrane system must be designed and constructed in accordance with the following limitations.

- nominally flat or pitched roofs and decks constructed to drain water to gutters and drainage outlets complying with the NZBC ;and
- with no steps within the deck level , no integral roof gardens and no down pipes direct discharge to the decks;and
- with the deck membranes continually protected from physical damage by a pedestal protection system.

New Zealand Building Code (NZBC)

The product will, if employed in accordance with the supplier's installation and maintenance requirements, assist with meeting the following provisions of the building code:

- **Clause B2 Durability:** Performance B2.3.1(b)
- **Clause E2 External moisture:** Performance E2.3.1, E2.3.2
- **Clause F2 Hazardous building materials:** Performance F2.3.1

Supporting Evidence

The product has and can make available the following additional evidence to support the above statements:



BRANZ Appraisal

[1043](#)

Product Criteria

Design requirements

Intended for roofs gutters parapets decks and balcony's. Falls must be built into the substrate.

- minimum falls , roofs 1 in 30 , decks 1:40 and gutters 1:100
- Allowance for deflection and settling must be designed
- Evolight S is impermeable therefore a means of dissipating construction moisture must be provided in the building design , in compliance with clause E2.3.6
- Drainage droppers must be used and fitted with a clamp and grate to reduce potential blockages.
- Penetrations and up-stands of the membranes must be raised above the level of the possible flooding caused by the blockage of the roof outlet.

masterspec partner

Company Contact Details



EXCLUSIVELY DISTRIBUTED BY MBP (NZ) LTD.

Company:	Mapei Products (MBP (NZ) Ltd)
Physical Address:	30 Fisher Crescent Mt Wellington AUCKLAND
Postal Address:	30 Fisher Crescent Mt Wellington AUCKLAND
Telephone:	64 09 9211994
Fax:	64 09 9211993
Email:	enquiries@mapei.co.nz
Website:	www.mapei.co.nz

Mapei Evolight S Roofing & Decking Membrane

Product Technical Statement: 109341



Installation requirements

Installation must be completed by installers , approved by MBP (NZ) Ltd. Installations of substrates must be completed by tradesman with an understanding of roof construction. Contractor solely responsible for workmanship

Maintenance requirements

The membrane system must be regularly checked for damage(annually) rubbish and debris.

Special care must be taken when inspecting the membrane roof system to ensure the continuing prevention of moisture ingress.

The care and maintenance document - provided by MBP (NZ) ltd - must be followed and maintained through the life of the roof , parapet gutter or balcony.

Warrantees

Durability warranty periods of 20 years will apply to the Evolight S Roofing and Decking system.

Company Product Information

Quality Assurance



ISO 9001 (Quality Management)

Relationships



Member of New Zealand Green Building Council



Date last validated: **06 July 2020**



Date last updated: **06 July 2020**

Disclaimer: The Product Technical Statement (PTS) template is copyright to Construction Information Limited. However the content of this PTS is the responsibility of the product manufacturer/supplier. Refer to the miproducts Terms and Conditions