

# DSD — Hardwood Decking Screw (Collated & Loose)

**Material & Finish**

316 Stainless Steel



**Size:** See the table below

**Features & Benefits**

- Low torque design for fast and easy driving.
- Broad head with nibs provides a greater clamping force and allows for a cleaner decorative finish.
- T25 and T30 6 Lobe recess provides a positive drive system, and attractive finish.
- A large countersunk head that holds the board firm, with nibs to help it embed cleanly and look aesthetically pleasing.
- A knurl or nib on the shank to allow for a clearance hole as the screw is installed, reducing driving torque and improving clamping force.
- For corrosion as well as ductility to allow hardwood timbers to move as they expand and contract.
- A drill point that will cut through the toughest of Hardwood timber with little chance of splitting, saving significant time for the builder.

**Applications**

- Hardwood decking
- This screw is available for both hand-drive and collated Quik Drive® system



**T25 or T30 6-lobe drive** recess provides a positive drive system, and attractive finish.



**Broad Head** with nibs provides a greater clamping force and allows for a cleaner decorative finish.



**Knurled Shank** creates a clearance hole in the board



**Hardwood Drill Point** will cut through the toughest of Hardwood timber with little chance of splitting, saving significant time for the builder

**Deck-Drive™**

**Specifications - Hand-drive**

Model No.	Size	Thread	Point	Material & Finish	Box Qty	Drive Size	Replacement Bit
SSDSD50R250	12G x 50mm	Coarse Threads	Hardwood Drill Point	316 Stainless Steel	250	T-25, 6-lobe	BIT25T-2-RC3
SSDSD50R1100					1100		
SSDSD65R250	12G x 65mm				250		
SSDSD65R1100					1100		
SSDSD1475R150	14G x 75mm				150	T-30, 6-lobe	BIT30T-2-RC3
SSDSD1475R400					400		
SSDSD14100R150	14G x 100mm				150		
SSDSD14100R400					400		



**Quik Drive®**

**Specifications - Quik Drive® Collated**

Model No.	Size	Thread	Point	Material & Finish	Box Qty	Drive Size	Replacement Bit
SSDSD50SA	12G x 50mm	Coarse Threads	Hardwood Drill Point	316 Stainless Steel	1000	T-25, 6-lobe	BITTX25-RC10
SSDSD65SA	12G x 65mm						

These coated fasteners possess a level of corrosion resistance that makes them suitable for use in some exterior and corrosive environments and with some preservative-treated timber. For applications in higher-exposure applications, consider Type-300 series stainless-steel fasteners for superior corrosion resistance. Bit(s) included with every box of screws. Pre-drilling and countersink may be necessary at ends, butt joints, and on applications where denser material is used. Follow board manufacturers recommendations where applicable.