# **HEAVENLY PERFORMANCE SERIES**

**TUBULAR DAYLIGHTING DEVICES** 

### DISTRIBUTED BY JUST LIFE GROUP LTD



SPECIFICATIONS	
Room Size:	12m2 (indicative only)
Recommended Maximum Tube Run:	9m
Diameter:	350mm
Recommended Maximum Ceiling Height:	< 3m
Minimum Roof Space:	N/A
Wind Zone:	High
Flashing Available:	5-45deg (proprietary flashing or tray) & <5deg (tray or curb mount)
Dome Technology:	Specially engineered clear dome for maximum light and strength
Tube Technology:	Miro silver tube
Reflectance:	98%

#### PRODUCT DESCRIPTION

Premium performing Tube Skylight. Available in 250mm & 350mm diameter

### **KEY BENEFITS**

- High performing during summer and when the sun is high in the sky.
- Unique triple glazed Lens
- Dimmable: With our daylight dimmer accessories you take control of the sun.
- Round corners and horizontally: With angle adapters and highly reflective tubes there are no barriers to where the light can go.
- Flexible install: Domes can be installed almost anywhere on your roof, they don't need to be right near the diffuser.
- Modern look: With multiple diffuser options to choose from including square there's a look to suit every space.
- Peace of mind: we offer 10 year product warranty when using our proprietary roof flashings

### **APPLICATIONS**

This system is suitable, but not limited to the following areas:

- Dark areas or internal rooms which require daylight
- · Bedroom, lounge, dining, kitchen, large bathrooms
- Internal room requiring daylight to meet building code G7
- · New builds and retrofit

### PRODUCT COMPLIANCE

• B2, E2, F2 and G7

# **ACCESSORIES**



Solar daylight dimmer 0-10V dimmer



LED light kit









A variety of decorative fixtures, add-ons and accessories available

### **LIMITATIONS**

- · Requires access to the roof.
- Tube length should be no longer than 9m.

# INSTALLATION TO BE CARRIED OUT BY AUTHORISED SOLATUBE LICENSEE

- Roof mounted flashing system and top collection dome to be installed before scaffolding and edge protection is removed if possible.
- Clear path, free of other services, is to be provided by the main contractor to the tubular daylight device's ceiling location.
- Solatube licensee to do final fit once ceiling has been installed and painted.
- Safe working at height practices to be followed.

# WARRANTY (SEE WARRANTY DETAILS FOR MORE INFORMATION)

10 Years LEAK PROOF GUARANTEE

5 Years for accessories

• 10 Years for materials and workmanship