



## Decking Board

MAX DEAD LOAD 25KG/m<sup>2</sup>

Max span for Live Loads

	2Kpa or 1.8 KN	3Kpa or 2.7KN	4Kpa or 2.7 KN
70 x 45 Joist Span	1.1m@ 600 ctr	0.9m @ 600 ctr	0.9m @ 600 ctr
70 x 45 Bearer Span	1.4m @ 1.1m ctr	1.1m@ .9m ctr	1.0m @ .9m ctr
70 x 90 Bearer Span	2.3m@ 1.1m ctr	1.9m@ .9m ctr	1.7m@ .9m ctr
50 x 150 Bearer Span	3.2m@ 1.1m ctr	2.6m@ .9m ctr	2.3m@ .9m ctr

## Structural Tile

MAX DEAD LOAD 48KG/m<sup>2</sup>

Max span for Live Loads

	2Kpa or 1.8 KN	3Kpa or 2.7KN	4Kpa or 2.7 KN
70 x 45 Joist Span	1.1m@ 600 ctr	0.8m @ 600 ctr	0.75m@ 600 ctr
70 x 45 Bearer Span	1.0m @ 1.1m ctr	0.7m@ 0.8 ctr	0.7m@ .75m ctr
70 x 90 Bearer Span	2.2m@ 1.1m ctr	1.8m@ .8m ctr	1.6m@ .75m ctr
50 x 150 Bearer Span	3.1m@ 1.1m ctr	2.5m@ .8m ctr	2.2m@ .75m ctr

ALL SPANS HAVE A 10% INCREASE WHEN SPANING 3 SUPPORTS OR MORE