

# PRODUCT CERTIFICATE



#### Product description

DriStud Wall Wrap is a white, water resistant, fire retardant, absorbent, breathable, flexible nonwoven building wrap. It is vapour permeable, enabling internal moisture to dissipate. The wall wrap is branded with the DriStud Wall Wrap branding and CodeMark logo.

### Product purpose or use

DriStud Wall Wrap is intended for use in new and existing buildings in conjunction with flexible flashing tapes. When installed with a flexible flashing tape, over a rigid air barrier or wall framing, DriStud Wall Wrap provides the secondary protective weather resistant laver which prevents external moisture from entering and accumulating in the wall structure.

#### Certificate holder

TCL Hunt Ltd 7 Fisher Cres, Mt Wellington, Auckland 1064 PO Box 132-166, Sylvia Park, Auckland, 1644 www.dristud.co.nz Ph +64 9 526 2700

## **CodeMark Product Certification Body**

Bureau Veritas Australia Pty Ltd 3/435 Williamstown Road. Port Melbourne VIC. 3207 Ph: 1800 855 190 www.bureauveritas.com.au

> Sam Guindi **Product Certification Manager**

For and on behalf of Bureau Veritas Australia Ptv Ltd This is to certify that

# **DriStud Wall Wrap**

## Complies with the New Zealand Building Code (NZBC):

If designed, used, installed and maintained in accordance with the scope of this certificate, the above mentioned product will meet or contribute to meeting the following provisions of the NZBC:

**Durability** B2.3.1 (a), B2.3.2 (a)

Fire Affecting Areas Beyond the Fire Source C3.4(c)

External Moisture E2.3.2. E2.3.7 **Hazardous Building Materials F2.3.1** 

Subject to the following conditions and limitations:

- 1. Must be installed in accordance with the DriStud Wall Wrap Installation Manual Rev 2. March 2019. This is available at www.dristud.co.nz
- 2. The scope of this certificate covers the use of DriStud Wall Wrap in buildings:
  - up to 10m in height, and
  - with a risk score less than 20, when evaluated against the E2/AS1 risk matrix, and
  - up to and including very high wind zone as defined in NZS 3604:2011, and
  - in all corrosion zones as defined in NZS3604:2011.
- 3. DriStud Wall Wrap is suitable for use with steel or timber framing
- May be installed in conjunction with direct fixed and cavity systems where absorbent or nonabsorbent claddings are specified.
- 5. The scope of the certificate covers the use of DriStud Wall Wrap with DriStud Cool Window Flashing Tape, DriStud Bozz Window Flashing Tape and rigid air barriers made from plywood. OSB or fibre cement.
- DriStud Wall Wrap can be exposed to UV for up to 60 days.



31 October 2019 Date of issue

CM70019 **Certificate Number** 



- This certificate is issued by an independent certification body accredited by JAS-ANZ, the product certification body appointed by the Chief Executive of the Ministry of Business, Innovation and Employment under the Building Act 2004. The Ministry does not in any way warrant, guarantee, or represent that the building method or product the subject of this certificates conforms with the New Zealand Building Code, nor accept any liability arising out of the use of the building method or product. The Ministry disclaims to the extent permitted by law, all liability (including negligence) for claims of losses, expenses, damages, and costs arising as a result of the use of the building method(s) or product(s) referred to in this certificate
- The certificate holder must maintain compliance with the conditions set out in section 15 of the Building (Product Certification) Regulations 2008. This certificate may only be reproduced in its entirety. It is advised to check that this certificate is currently valid and not withdrawn or suspended by referring to the Register of Product Certificates on the Building Performance website http://www.building.govt.nz.