




# BROWNSTONE OAK INTERIOR PANELLING SPECIFICATION SHEET



Brownstone Oak

Imondi Brownstone Oak T&G Interior Panelling by Forté.  
21mm thick, 50-230mm wide and 400-2200mm length.  
Glue or pin onto substrate. Reclaimed wood, pre-finished  
with natural oil.

## PRODUCT DETAILS

|                 |  |
|-----------------|--|
| Collection      | Imondi   |
| Product Type    | Engineered Plank                                 |
| Availability    | Stocked  |
| Total Thickness | 21mm   |
| Width           | 50-230mm   |
| Length          | 400-2200mm                                       |
| Wear Layer      | 6mm reclaimed oak                                |
| Core            | Ply  |
| Construction    | Multi-layer engineered                           |
| Surface Texture | Rough sawn texture with circular<br>saw markings |
| Edge Style      | Square edge                                      |
| Status          | Pre-finished                                     |
| Finish          | Natural oil                                      |
| Specie          | Reclaimed Oak                                    |
| Wood Grade      | Reclaimed Rustic                                 |

## STRUCTURAL WARRANTY

|                     |  |
|---------------------|--|
| Lifetime Structural | For terms and conditions see<br><a href="http://www.forte.co.nz/warranties">www.forte.co.nz/warranties</a> |
|---------------------|--|

## SUSTAINABILITY

|                        |                      |
|------------------------|----------------------|
| FSC® Certification     | Available on request |
| LEED® points available |                      |

## INSTALLATION

|                       |   |
|-----------------------|---|
| Installation Method   | Glue down or secret pin   |
| Suitable Substrates   | Plaster board, Plywood, MDF board -<br>enquire for others                 |
| Joint Profile         | Tongue & Groove   |
| Suitable Applications | Interior walls, ceilings  |
| Suitable Uses         | Residential homes, hospitality, retail<br>stores, restaurants, apartments |
| Wet Area Suitability  | Contact the Forté team for information<br>0508 35 66 77                   |

## TECHNICAL SPECIFICATIONS

|   |   |
|---|---|
| NZBC Fire Ratings<br>(Walls and Ceilings) | Group 3 Note: Fire-shield can be<br>applied to meet Group 1-S |
| Reaction to Fire (Walls<br>and Ceilings)  | Class Cfl - S1  |
| Timber Density                            | 650kg/m <sup>3</sup>  |
| Formaldehyde Emission                     | E1  |

# Care and Maintenance

RESIDENTIAL AND COMMERCIAL CARE AND MAINTENANCE

---

Please visit [www.forte.co.nz/advice/timber-wall-and-ceiling-panelling-care-and-maintenance-guide](http://www.forte.co.nz/advice/timber-wall-and-ceiling-panelling-care-and-maintenance-guide)

# Structural Warranty

IMONDI LIFETIME STRUCTURAL WARRANTY

---

The Imondi Collection comes with a Lifetime Structural Warranty. For full warranty terms and conditions, please visit [www.forte.co.nz/warranties](http://www.forte.co.nz/warranties)

# Installation

THE IMONDI COLLECTION MUST BE INSTALLED BY A TRAINED PROFESSIONAL

---

Please ensure that you have read and understood the installation guidelines before proceeding to install Imondi Interior Panelling. If you have any questions or concerns, please call the Forté technical team on 0508 35 66 77. Failure to adhere to the Forté Installation Guidelines may void your warranty.

For full installation guidelines, please visit [www.forte.co.nz/installation](http://www.forte.co.nz/installation)



# WEATHERED OAK INTERIOR PANNELLING SPECIFICATION SHEET



Weathered Oak

Imondi Weathered Oak T&G Interior Panelling by Forté.  
15mm thick, 95-135mm wide and 400-2200mm length.  
Glue or pin onto substrate. Reclaimed wood, pre-finished  
with natural oil.

## PRODUCT DETAILS

|                 |  |
|-----------------|--|
| Collection      | Imondi   |
| Product Type    | Engineered Plank                                 |
| Availability    | Stocked  |
| Total Thickness | 15mm   |
| Width           | 95-135mm   |
| Length          | 400-2200mm                                       |
| Wear Layer      | 4mm reclaimed oak                                |
| Core            | Ply  |
| Construction    | Multi-layer engineered                           |
| Surface Texture | Rough sawn texture with sporadic<br>saw markings |
| Edge Style      | Square edge                                      |
| Status          | Pre-finished                                     |
| Finish          | Natural oil                                      |
| Species         | Reclaimed Oak                                    |
| Wood Grade      | Reclaimed Rustic                                 |

## STRUCTURAL WARRANTY

|                     |  |
|---------------------|--|
| Lifetime Structural | For terms and conditions see<br><a href="http://www.forte.co.nz/warranties">www.forte.co.nz/warranties</a> |
|---------------------|--|

## SUSTAINABILITY

|                        |                      |
|------------------------|----------------------|
| FSC® Certification     | Available on request |
| LEED® points available |                      |

## INSTALLATION

|                       |   |
|-----------------------|---|
| Installation Method   | Glue down or secret pin   |
| Suitable Substrates   | Plaster board, Plywood, MDF board -<br>enquire for others                 |
| Joint Profile         | Tongue & Groove   |
| Suitable Applications | Interior walls, ceilings  |
| Suitable Uses         | Residential homes, hospitality, retail<br>stores, restaurants, apartments |
| Wet Area Suitability  | Contact the Forté team for information<br>0508 35 66 77                   |

## TECHNICAL SPECIFICATIONS

|   |   |
|---|---|
| NZBC Fire Ratings<br>(Walls and Ceilings) | Group 3 Note: Fire-shield can be<br>applied to meet Group 1-S |
| Reaction to Fire (Walls<br>and Ceilings)  | Class Cfl - S1  |
| Timber Density                            | 650kg/m <sup>3</sup>  |
| Formaldehyde Emission                     | E1  |

# Care and Maintenance

RESIDENTIAL AND COMMERCIAL CARE AND MAINTENANCE

---

Please visit [www.forte.co.nz/advice/timber-wall-and-ceiling-panelling-care-and-maintenance-guide](http://www.forte.co.nz/advice/timber-wall-and-ceiling-panelling-care-and-maintenance-guide)

# Structural Warranty

IMONDI LIFETIME STRUCTURAL WARRANTY

---

The Imondi Collection comes with a Lifetime Structural Warranty. For full warranty terms and conditions, please visit [www.forte.co.nz/warranties](http://www.forte.co.nz/warranties)

# Installation

THE IMONDI COLLECTION MUST BE INSTALLED BY A TRAINED PROFESSIONAL

---

Please ensure that you have read and understood the installation guidelines before proceeding to install Imondi Interior Panelling. If you have any questions or concerns, please call the Forté technical team on 0508 35 66 77. Failure to adhere to the Forté Installation Guidelines may void your warranty.

For full installation guidelines, please visit [www.forte.co.nz/installation](http://www.forte.co.nz/installation)