



SECURA

Fence panel and pedestrian gate

Built tough and made to last, the Secura fence panel provides an excellent deterrent to would-be intruders, combining a double top rail for added strength, large vertical bars, and additional spikes on top. With excellent low maintenance durability, security, and adaptability, Secura has all the design features needed for security fencing and the versatility to suit any site.

FEATURES:

- Heavy duty aluminium construction
- Spiked top to deter climbing
- 100mm anti-climb gap in vertical bars
- Exclusively available as raking panel up to 20 degrees
- Black powder coated finish as standard. Custom colours available on request
- Spiked top can easily be removed for a non-threatening appearance
- Brackets and hardware supplied
- Ex Stock standard sized fence panels and pedestrian gates
- Width and height adjustable pedestrian and driveway gates
- Gate automation and access control systems available

IDEAL FOR:

- Security fencing
- Road frontages
- Commercial
- Industrial
- Civil
- Schools (spikes removed)

SPECIFICATION DETAILS - EXSTOCK

FENCE PANEL

Heights:	1800mm, 2100mm
Width:	2350mm
Horizontals:	40 x 40mm
Verticals:	25 x 25mm, 100mm spacing
Posts:	65 x 65mm, aluminium or galvanized steel
Raking panels:	Yes, up to 20 degrees
Fixing options:	Inground, side fixed and base plated

PEDESTRIAN GATE

Height:	1800mm, 2100mm
Width:	1200mm
Horizontals:	40 x 40mm
Verticals:	25 x 25mm, 100mm spacing
Posts:	65 x 65mm, galvanized steel

PRODUCT PROPERTIES

Material:	Aluminium, Galvanized Steel
Finish:	Powder coat
Colour:	Black, Custom

COMPLIANCE INFORMATION:

Compliant with NZ Building Code F4 Safety from falling when installed with steel posts at up to 1240mm post centers.
Compliant with NZ Building Code F9 Restricted access to residential pools when installed at up to 2415mm post centers.

Site Specific PS1 available on request.

Suitable for installation in up to Very High Wind Zones.

CARE & MAINTENANCE:

To best care for your fence, meet warranty requirements and to extend the life of our products we recommend washing down all exposed metalwork including panels, posts, gates and fixings every 6 months, and every 3 months in sea spray and geothermal locations.

For full care and maintenance information and instructions please see the Urban Group Care and Maintenance document.

WARRANTY INFORMATION:

We provide a 10year warranty on aluminium fence panels, posts and gates, 5years on galvanized steel posts and 2years on associated hardware.

These warranty periods are subject to further terms and conditions, please see the Urban Group Warranty 2023 document for full warranty information.

Please ensure the current Data Sheet is consulted prior to specification or installation of Urban Group products. If you require additional information not included in this Data Sheet, please contact Urban Group.