



RESIDENTIAL TRIMRIB® ROOFING

INTERNAL WELDED ALUMINIUM BARGE TRANSITION FLASHING

Detail Number: RI-RTR-210B

Date drawn: 16/12/2024



TRANSITION FLASHING

SUITABLE FOR PITCHES OF MINIMUM 10°. FOR LOWER PITCHES USE BACK FLASHING TO RIDGE

WELDED ALUMINIUM TRANSITIONAL FLASHING SEAL TO SUIT PROFILE

GENERAL NOTES:

- These details are to be read with Roofing Industries Trimrib Product Technical Statement.
- The building designer is ultimately responsible to ensure that the details used meet the requirements of the NZ Building Code for the specific project.
- Details of the supporting structure (including cavity battens if used) are indicative only and are the responsibility of the building designer. For steel framed buildings thermal break cavity battens may be required.
- Roof/wall underlay selection are the responsibility of the designer. Underlay to be installed in accordance with underlay manufacturer's recommendations and requirements.
- These details are for Roofing Industries profile/s as nominated and may not be applicable to other profiles.
- This drawing is the copyright of 'Roofing Industries' and can only be copied or reproduced with their permission.
- Further information can be obtained from the NZ Metal Roof & Wall Cladding Code of Practice: www.metalroofing.org.nz or E2/AS1 where applicable.
- Details are for steel-based materials, other substrates may require some changes.
- All dimensions are nominal.
- Fixings: The designer needs to check the screw manufacturer's technical data of the selected screw type for the design wind load and the material being fastened to.

Copyright detail © 2024

