Rhythmic

Belgotex[®]

Stain Proof Fade Proof Environmentally Anti-	static Suitable For Underfloor Heating Suitable For Stairs Anti-Allegenic Castor Chair Compatible S00 x 500mm
Construction	Patterned Tufted Loop Pile
Yarn	100% Stainproof SDX (Solution Dyed Nylon)
Size	500mm x 500mm
Tiles per Carton	20pcs / 5.0m²
Pile Weight	475g/m ²
Total Weight	± 3820 g/m²
Pile Height	2.0mm
Total Thickness	8.0mm
Machine Gauge	1/10th
Backing	EcoBac
Electrical Properties	Antistatic
Electrical Propensity	≤ 2kV (ISO 6356 & EN 1307)
Anti-allergenic Properties	Will not shed or pill. Resistant to mould & mildew.
Acoustic Insulation	28dB (EN ISO 10140)
Acoustic Absorption	αω 0.30 (ISO 354)
Underfloor Heating	Suitable
Fire Rating	CRF 8.3kW/m ² (ISO 9239-1)
VOC Rating	Pass (GBCSA/GLP Criteria)
Colour Fastness	Light 8 (ISO 105 - B02) Rubbing Wet 4 - 5 (ISO 105 - X12) Dry 4 - 5 (ISO 105 - X12) Water 4 - 5 (ISO 105 - E01)
Classification	Heavy Duty Commercial
Light Reflective Value (LRV)	Wave 4.49 Rock 5.71 Regular 11.52 Pitch 14.90 Drum 16.27 Even 23.63
Stair Rating	Suitable
Warranty	15 Year Commercial Warranty
Environmental	GreenStar Low VOC, solution dying uses no water. ISO 14001
Installation	Laying recommendation: Monolithic, Quarter Turn, Ashlar or Brick. Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. Must be laid in accordance with AS/NZ Installation Standards.

■ For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz

Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances.

Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.