



Construction	Heterogeneous Sheet Vinyl
Width	2.0m
Standard Roll Length	25m
Pattern Repeat	Refer to Vinyl Range Statement
Total Weight	2543g/m <sup>2</sup>
Wearlayer Thickness	0.7mm
Total Thickness	2.0mm
Wear layer PUR treatment	HyperGuard+
Slip Resistance	DS-R10 (DIN 51130)
Electrical Properties	Antistatic
Electrical Propensity	<2kV (EN 1815)
Fire Rating	ISO 9239-1
Acoustic Insulation	ΔLw 7 dB (ISO 717-2)
Dimensional Stability	0.05% (EN ISO 23999)
Curling	≤8mm (EN ISO 23999)
Thermal Insulation	0.25W/mK (EN ISO 10456)
Indoor Air Quality	A+ Emissions
Residual Indentation	0.05mm (EN ISO 24343-1)
Underfloor Heating	Suitable
Chemical Resistance	Very Good (EN ISO 26987)
Abrasion Group	Class T (EN 660-2)
Classification	Class 23 Domestic Heavy/ Class 34 Commercial Very Heavy/ Class 43 Industrial Heavy
Warranty	15 Year Residential Warranty 10 Year Commercial Warranty
Environmental	REACH Certificate of Compliance ISO 9001
Installation	Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. Must be laid in accordance with AS/NZ Installation Standards.

- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances.
- This product is intended for use solely as an indoor floor covering and is not recommended or sold for any other purpose.
- Use entryway systems outside each entrance to prevent dirt, sand, grit and other substances from being tracked onto floor.
- **Rubber Migration:** Rubber migration (also known as Plasticiser Migration) is a condition that can cause vinyl to discolour. It is caused by rubber or latex products, eg rubber or latex-soled slippers, shoes and rubber backed mats, coming to contact with the vinyl over a constant period of time. It is neither a manufacturing nor an installation fault and therefore is not covered by our warranties.
- Plain, granite or patterned vinyls will either need to be reverse laid or a wider width should be used to allow for colour inequality, an additional allowance may have to be made for the pattern repeat.