



<b>Construction</b>	Patterned Tufted Loop Pile	
<b>Yarn</b>	100% Stainproof SDX (Solution Dyed Nylon)	
<b>Size</b>	500mm x 500mm	
<b>Tiles per Carton</b>	20pcs / 5.0m <sup>2</sup>	
<b>Pile Weight</b>	475g/m <sup>2</sup>	
<b>Total Weight</b>	± 3600 g/m <sup>2</sup>	
<b>Pile Height</b>	2.0mm	
<b>Total Thickness</b>	6.0mm	
<b>Machine Gauge</b>	1/10th	
<b>Backing</b>	Bitumen	
<b>Electrical Properties</b>	Antistatic	
<b>Electrical Propensity</b>	< 2kV (ISO 6356 & EN 1307)	
<b>Anti-allergenic Properties</b>	Will not shed or pill. Resistant to mould & mildew.	
<b>Acoustic Insulation</b>	28dB (EN ISO 10140)	
<b>Acoustic Absorption</b>	α 0.30 (ISO 354)	
<b>Underfloor Heating</b>	Suitable	
<b>Fire Rating</b>	CRF 8.3kW/m <sup>2</sup> (ISO 9239-1)	
<b>VOC Rating</b>	Pass (GBCSA/GLP Criteria)	
<b>Colour Fastness</b>	<b>Light</b>	7 (ISO 105 - B02)
	<b>Rubbing</b>	Wet 4 - 5 (ISO 105 - X12) Dry 4 - 5 (ISO 105 - X12)
	<b>Water</b>	4 - 5 (ISO 105 - E01)
<b>Classification</b>	Heavy Duty Commercial	
<b>Light Reflective Value (LRV)</b>	Midnight	19.2
	Thunder	4.42
	Sunset	4.91
	Horizon	5.17
	Sunrise	5.66
	Cloud Break	9.31
<b>Stair Rating</b>	Suitable	
<b>Warranty</b>	15 Year Commercial Warranty	
<b>Environmental</b>	Greentag Certified, GreenStar, Homestar™, Well Building Standard® Low VOC, solution dyeing uses no water. ISO 14001	
<b>Installation</b>	Laying recommendation: Quarter turn. Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. Must be laid in accordance with AS/NZ Installation Standards.	

- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances.
- Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.