



PRODUCT DESCRIPTION

Roof mounted fan system with proprietary flashing and vent cap on the roof line to provide wet room extract ventilation.

KEY BENEFITS

- Efficient Operation: Roof penetrations often offer the path of least resistance for ducting which in turn leads to more efficient performance from fans.
- Quieter performance: Remote mounted fans mean the noise and vibration is further away from the occupant, not at the perimeter of the space.
- Peace of mind: backed up by a 10-year leak proof guarantee.

APPLICATIONS

*This system is suitable for, but not limited to the following areas:

- Single level / top floor installations.
- Bathrooms, toilets, internal laundries.

PRODUCT COMPLIANCE

- G4: Extract air volume exceeds 25l/s for bathrooms and/or 40l/s for laundries.
- Healthy Homes: Bathroom Ventilation
- B2, E2
- BRANZ appraisal 665

ELECTRICAL

- Electrical connection excluded.
- All fans to be connected to an isolating switch as per AS/NZS 3000:2018.

WARRANTY

- 10 Year LEAK PROOF GUARANTEE
- 10 Years for materials and workmanship
- 2 Years for fan motor

Terms and conditions apply.

SPECIFICATIONS

Air Flow:	45l/s
Diameter:	150dia
Duct Run:	Up to 3m
Noise :	45dB @ 0.5m
Install Location:	Wet rooms
Minimum Clearance:	250mm, options for skillion ceilings
Rooms Served:	One
Ventilation Type:	Intermittent Extract
Filter:	NA
Control:	Wall Switch, Single Speed
Power:	35W
Add-ons:	<ul style="list-style-type: none"> • Timer • Humidity Sensor

EXPANSIONS / ALTERNATIVES

- HTBKTRFC : For fire rated ceiling applications
- HTBKTRIL : Alternative using inline fan
- HTBKTRSK : Alternative for use in no cavity/skillion ceiling applications

