

PRODUCT OVERVIEW



PRODUCT NAME		OL 100 LED 3K	AOL 100 LED 3K	OL 100 LED 5K	AOL 100 LED 5K	OL 200 LED 5K	AOL 200 LED 5K
Product number	black	EL10710711	EL10750717	EL10710018	EL10750014	EL10710117	EL10750113
	white	EL10710704	EL10750700	EL10710001	EL10750007	EL10710100	EL10750106
Mains voltage		230 V AC 50 Hz	230 V AC 50 Hz	230 V AC 50 Hz	230 V AC 50 Hz	230 V AC 50 Hz	230 V AC 50 Hz
Power consumption	light	14 W	14 W	14 W	14 W	25 W	25 W
Illuminant		6 LEDs	6 LEDs	6 LEDs	6 LEDs	12 LEDs	12 LEDs
Light colour		approx. 3000 K (warm white)	approx. 3000 K (warm white)	approx. 5,000 K (white)	approx. 5,000 K (white)	approx. 5,000 K (white)	approx. 5,000 K (white)
Luminous flux	light	675 lm	675 lm	770 lm	770 lm	1610 lm	1610 lm
Luminous efficacy	light	48 lm/W	48 lm/W	55 lm/W	55 lm/W	64 lm/W	64 lm/W
Overall efficiency of electronics		0,95	0,95	0,95	0,95	0,95	0,95
Permissible ambient temperature		-25 °C to +50 °C	-25 °C to +50 °C	-25 °C to +50 °C	-25 °C to +50 °C	-25 °C to +50 °C	-25 °C to +50 °C
Housing material		Die-cast aluminium and plastic	Die-cast aluminium and plastic	Die-cast aluminium and plastic	Die-cast aluminium and plastic	Die-cast aluminium and plastic	Die-cast aluminium and plastic
Protection type		IP 55	IP 55	IP 55	IP 55	IP 55	IP 55
Protection class		II	II	II	II	II	II
Installation type		Wall mounting	Wall mounting	Wall mounting	Wall mounting	Wall mounting	Wall mounting
Dimensions approx. height x width x length (mm)		205 x 104 x 143	205 x 104 x 143	205 x 104 x 143	205 x 104 x 143	205 x 184 x 143	205 x 184 x 143
For models with a motion detectorfield of detection		–	140°	–	140°	–	140°
	range (at recommended installation height of 1.80 m)	–	10 m	–	10 m	–	10 m
	range (at recommended installation height of 2.50 m)	–	–	–	–	–	–

Technical and design features may be subject to change without notice.

This luminaire contains built-in LED lamps. The lamps cannot be changed in the luminaire.