

TBA Protective Technologies

Australia Head Office

Unit 12, 8 Leighton Place
Hornsby, NSW, 2077



TBA Firefly Head

Office

P.O. BOX 52
Laidley
QLD, 4341
Australia

Contact Us

Phone: (07) 5411 4209

Mobile: 0400 966 899

Email: trevor@tbafirefly.com.au



MATERIAL DESCRIPTION

Titan Cavity Fire Barrier is a flexible and lightweight fabric with an inner core of insulating fire protection. Acoustic Performance = 49dB room to room.

CERTIFICATION

AS1530.1 Non-Combustibility

CSIRO Report No: FNC11220

Tested and assessed in accordance with:

AS1530.4-2005 and AS4072.1-2005

Exova Warringtonfire Report No: 22766

UNIT OF MEASURE

ROLL

SIZE

6m x 1.3m = 7.8m²

15mm Thick

WEIGHT

3.9kg per m²

FRL 60/60/60
OR
FRL -/120/60

TITAN

APPLICATIONS

This easy to install flexible fire barrier is used as a DTS solution to provide a seal of up to 6.3m high x infinite length, which extends from the head of a compartment wall/sub division wall to the underside of the roof lining. Can also be used to cap off lift shafts and stair wells, along with service risers for horizontal applications. Flexibility and fire rating level makes this product perfect for bespoke applications.



Fire Escape Stairwells-
Civic Centre Christchurch



Roof Compartment Fire Barrier



Curved External Wall
- Aquatic Centre NSW