

modulyss® carpet tiles

BPIR Declaration

Version: November 23

Designated building product: Class 1

Heritage Carpets Limited has provided this declaration to satisfy the provisions of Schedule 1(d) of the Building (Building Product Information Requirements) Regulations 2022.

Product/System

Name	modulyss carpet tiles
Line	All tufted Carpet tiles from modulyss
Identifier	modulyss carpet tiles

Description

modulyss carpet tiles made with nylon (PA) pile material with various backing options. These carpet tiles may have a loop pile or cut pile surface finish and can be plain or patterned. modulyss carpet tiles are 500mm square by default but are available with other dimensions.

All modulyss carpet tiles have compliant, similar performance and fire characteristics, including anti-static.



Scope of use

modulyss carpet tiles **are suitable** for use indoors in high use environments including:

Commercial / Civic

Residential / Accommodation

Education

Health

Infrastructure (indoors)

They are suitable for use with castor chairs

They are suitable for use with underfloor heating and,

Can be installed over most clean, flat and dry surfaces.

They **are not** suitable for use:

On walls

In food preparation areas

In wet areas

Outdoors

Conditions of use

The carpet tiles must be installed in accordance with the modulyss installation guidelines and must be cleaned and maintained in accordance with the modulyss cleaning recommendations.

Accordingly, modulyss' installation and maintenance guidance are available on our website.

A suitable Low VOC pressure sensitive adhesive may be used and a locally available example is Gilt Edge Gilt Grip 66.

Contributions to compliance -Relevant building code clauses

modulyss carpet tiles satisfy **B2-Durability**

B2.3.1 (c) refers to easily replaced finishes

modulyss heavy traffic carpet tiles properly installed and maintained indoors will outlast the expectation of this clause.

A draft warranty is available on our website to confirm the above.

Modulyss carpet tiles also carry an EN 14041 CE mark under EN1307 confirming the minimum 5-year durability requirement.

modulyss carpet tiles satisfy **C3-Fire affecting areas beyond the source**

C3.4 (b) refers to floor surface materials

All modulyss carpet tiles exceed the highest test result required under this section of the act being 4.5kW/m² when tested to ISO9239-1: 2010

The relevant test certificate is linked on our website

modulyss carpet tiles satisfy **D1- Access Routes**

D1.3.3 (d) refers to adequate slip resistance

According to Table 2 in D1/AS1 all carpets are considered to have both acceptable dry slip resistance and acceptable wet slip resistance.

See the table on p24 of the act [here](#)

modulyss carpet tiles are not subject to a warning or ban under **S26- Warnings and Bans**

For further information supporting modulyss carpet tiles claims please refer to our website or reach out to us personally.

Contact details

Manufacture location	Overseas
Legal and trading name of manufacturer	modulyss
Manufacturer's Address for Service	Zevensterrestraat 21, 9240 Zele, Belgium
Manufacturer's Web / Contact	https://modulyss.com/en-INT/contact
Legal and trading name of importer	Heritage Carpets Limited
Importer address for service	155 New North Road Eden Terrace, Auckland 1021
Importer website	www.heritagecarpets.co.nz
Importer NZBN	9429033288758
Importer email	office@heritagecarpets.co.nz
Importer phone number	+64 9 362 0427

Responsible person

As the responsible person as set out in Regulation 3, I confirm that the information supplied in this declaration is based on information supplied to the company as well as the company's own processes and is therefore to the best of my knowledge, correct.

Signed for and on behalf of **Heritage Carpets Limited**:



Umesh Dayal
Director
November 2023

HERITAGE CARPETS LIMITED

155 New North Road Eden Terrace, Auckland 1021 New Zealand
+64 9 362 0427 | www.heritagecarpets.co.nz