

## **Product Information Declaration**

## **Karndean Knight Tile Wood Range**

### **Range Description**

This Jacobsen Product Information Declaration (PID) applies to the luxury vinyl tiles (lvt) range sold by Jacobsen as Karndean Knight Tile Wood

### **Identifiers**

See individual sku codes under identifiers

### **Scope and Limitations of Intended Use**

<u> </u>	Residential	×	Commercial	<b>✓</b>	Interior	×	Exterior
×	High Traffic	×	<del>Low Traffic</del>	×	Exposed Sunlight	×	Wet Areas
×	Antistatic Environment	×	Food Prep Areas	×	<del>Clean Room</del>	<b>✓</b>	With Wheels
×	Ramp/Entry	<u> </u>	Under Floor Heating	×	Over Existing Floor		

### B

### **Stability**

Relevant NZBC Clause	Product Performance
B2.3.1(c)	Lifetime Residential, 10 years Light Commercial
Residential	23 (ISO 10874)
Commercial	31 Moderate (ISO 10874)
Industrial	_

### C

### **Protection from Fire**

Relevant NZBC Clause	Product Performance		
C3.4			
C3.4 (a) Wall	Has not been tested		
C3.4 (b) Floor	-		

### Access

Relevant NZBC Clause	Product Performance		
D1.3.3			
Level Surface (Wet)	-		
Level Surface (Dry)	-		
Suitable for food prep	-		

## Ε

### Moisture

Relevant NZBC Clause	Product Performance
E3.3.3	Impervious and easily cleaned
E3.3.5	Impervious and easily cleaned
E3.3.6	Water resistant
NZBC/AS1	-

## F

### **Safety of Users**

Relevant NZBC Clause	Product Performance
F2.3.1	Low VOC
	Does not encourage bacterial growth
	Phthalate-free
Indoor Air Quality	Optimal

## G

### **Services and Facilities**

Relevant NZBC Clause	Product Performance		
G3.3.2 (b)	Water resistant		
G6.3.2	-		

## Н

### **Energy Efficiency**

Relevant NZBC Clause Product Performance

Thermal Rating -

## X

### **Warnings and Bans**

Building Act 2004 Product Performance
Section 26 -

### **Supporting Documents**

All supporting documents can be found on the Jacobsen website, <u>jacobsen.co.nz</u> or by this QR code

Page 1 of 3 V:230924

# **Product Information Declaration Karndean Knight Tile Wood Range**

### B2 3.1

Building elements must, with only normal maintenance, continue to satisfy the performance requirements of this code for the lesser of the specified intended life of the building, if stated, or:

(c)

5 years if:

- 1. the building elements (including services, linings, renewable protective coatings, and fixtures) are easy to access and replace, and
- 2. failure of those building elements to comply with the building code would be easily detected during normal use of the building.

### C3.4

Surface Linings

(b)

floor surface materials in the following areas of buildings must meet the performance criteria specified below:

### D1.3.3

Access routes shall:

(d)

have adequate slip-resistant walking surfaces under all conditions of normal use.

### E3.3.3

Floor surfaces of any space containing sanitary fixtures or sanitary appliances must be impervious and easily cleaned.

### E3.3.5

Surfaces of building elements likely to be splashed or become contaminated in the course of the intended use of the building, must be impervious and easily cleaned.

### E3.3.6

Surfaces of building elements likely to be splashed must be constructed in a way that prevents water splash from penetrating behind linings or into concealed spaces.

### F2.3.1

The quantities of gas, liquid, radiation or solid particles emitted by materials used in the construction of buildings, shall not give rise to harmful concentrations at the surface of the material where the material is exposed, or in the atmosphere of any space.

### G3.3.2

Spaces for food preparation and utensil washing shall have:

### (b

all building elements constructed with materials which are free from hazardous substances which could cause contamination to the building contents

### G6.3.1

The Sound Transmission Class of walls, floors and ceilings, shall be no less than 55.

### G6.3.2

The Impact Insulation Class of floors shall be no less than 55.

#### H1

This clause requires enclosed spaces where temperature or humidity are modified to provide adequate thermal resistance and to limit uncontrollable airflow in certain buildings.

## **Note**

It is expected that **Karndean Knight Tile Wood** is installed, cleaned and maintained according to instructions and best practice guides housed on the product page.

All products may be subject to fading if exposed to excessive, unfiltered UV light.

Page 2 of 3 V:230924

# **Product Information Declaration Karndean Knight Tile Wood Range**

### **Identifiers**

This JPID covers all colours from Karndean Knight Tile Wood including:

Lime Washed Oak 28053 Medium Limed Oak 28052 Rose Washed Oak 28051 Pale Limed Oak 28050 Coastal Blackbutt 28049 Nordic Limed Oak 28048 Shadow Studio Oak 28047 Classic Spotted Gum 28046 Coastline Oak 28045 Traditional Character Oak 28044 Washed Character Oak 28043 Blond Character Oak 28042 Urban Spotted Gum 28041 Grey Limed Oak 28040 White Painted Oak 28039 Light Worn Oak 28038

Lime Washed Oak 27680 Medium Limed Oak 27679 Rose Washed Oak 27678 Pale Limed Oak 27677 Coastal Blackbutt 27676 Nordic Limed Oak 27675 Shadow Studio Oak 27674 Classic Spotted Gum 27673 Coastline Oak 27672 Traditional Character Oak 27671 Washed Character Oak 27670 Blond Character Oak 27669 Urban Spotted Gum 27668 Grey Limed Oak 27667 White Painted Oak 27666 Light Worn Oak 27665

### **Sustainability**

Rating System	Rating	Product Performance
Green Star Design &	Credit 12	-
As Built NZ (V1)	Credit 20	1 Point
	Credit 21	0.75 Points
Green Star	Credit 13	-
Interiors NZ (V1)	Credit 20	1 Point
	Credit 21	0.75 Points
Green Star Credit 21 Performance NZ (V1)		1 Point
Homestar V5	HC 7	1 Point
	EN 3	1.5 Points
Homestar V4	Mat-1	2 Points
	Mat-2	1 Point
Environmental Product D	Deceleration	-
Embodied Carbon Emiss	sion Data	GD 8.91kg CO2 eq RC 14.98kg CO2 eq

### **Environmental Credentials**

## **Jacobsen®**

Jacobsen 41D Morrin Road, St Johns, 1072 0800 800 460 jacobsen.co.nz sales@jacobsen.co.nz

NZBN: 9429040403328



Product Manufacturer: Karndean Country of Origin: China

Page 3 of 3 V:230924