

Product Information Declaration

Karndean Opus Plank Range

Range Description

This Jacobsen Product Information Declaration (PID) applies to the luxury vinyl tiles (lvt) range sold by Jacobsen as Karndean Opus Plank

Identifiers

See individual sku codes under identifiers

Scope and Limitations of Intended Use

<u> </u>	Residential	✓ Commercial ✓ Interior X Exterior	
~	High Traffic	X Low-Traffie X Exposed-Sunlight X Wet-Areas	
×	Antistatic Environment	X Food Prep Areas X Glean Room ✓ With Wheels	i
×	Ramp/Entry	✓ Under Floor Heating X Over Existing Floor	

B

Stability

Relevant NZBC Clause	Product Performance	
B2.3.1(c)	Lifetime Residential, 15 years Commercial	
Residential	23 (ISO 10874)	
Commercial	33 Heavy (ISO 10874)	
Industrial	-	

Protection from Fire

Relevant NZBC Clause	Product Performance	
C3.4		
C3.4 (a) Wall	Has not been tested	
C3.4 (b) Floor	-	

D

Access

Relevant NZBC Clause	Product Performance	
D1.3.3		
Level Surface (Wet)	-	
Level Surface (Dry)	-	
Suitable for food prep	-	

F

Moisture

Relevant NZBC Clause	Product Performance
E3.3.3	Impervious and easily cleaned
E3.3.5	Impervious and easily cleaned
E3.3.6	Water resistant
NZBC/AS1	_

F

Safety of Users

Relevant NZBC Clause	Product Performance	
F2.3.1	Low VOC	
	Does not encourage bacterial growth	
	Phthalate-free	
Indoor Air Quality	Optimal	

G

Services and Facilities

Relevant NZBC Clause	Product Performance
G3.3.2 (b)	Water resistant
G6.3.2	-

Н

Energy Efficiency

Relevant NZBC Clause	Product Performance	
Thermal Rating	0.0097 m2 K/W (ISO 8302)	

X

Warnings and Bans

Building Act 2004	Product Performance	
Section 26	-	

Supporting Documents

All supporting documents can be found on the Jacobsen website, <u>jacobsen.co.nz</u> or by this QR code

Page 1 of 3 V:230924

Product Information Declaration Karndean Opus Plank Range

B2 3.1

Building elements must, with only normal maintenance, continue to satisfy the performance requirements of this code for the lesser of the specified intended life of the building, if stated, or:

(c)

5 years if:

- 1. the building elements (including services, linings, renewable protective coatings, and fixtures) are easy to access and replace, and
- 2. failure of those building elements to comply with the building code would be easily detected during normal use of the building.

C3.4

Surface Linings

(b)

floor surface materials in the following areas of buildings must meet the performance criteria specified below:

D1.3.3

Access routes shall:

(d)

have adequate slip-resistant walking surfaces under all conditions of normal use.

E3.3.3

Floor surfaces of any space containing sanitary fixtures or sanitary appliances must be impervious and easily cleaned.

E3.3.5

Surfaces of building elements likely to be splashed or become contaminated in the course of the intended use of the building, must be impervious and easily cleaned.

E3.3.6

Surfaces of building elements likely to be splashed must be constructed in a way that prevents water splash from penetrating behind linings or into concealed spaces.

F2.3.1

The quantities of gas, liquid, radiation or solid particles emitted by materials used in the construction of buildings, shall not give rise to harmful concentrations at the surface of the material where the material is exposed, or in the atmosphere of any space.

G3.3.2

Spaces for food preparation and utensil washing shall have:

(b

all building elements constructed with materials which are free from hazardous substances which could cause contamination to the building contents

G6.3.1

The Sound Transmission Class of walls, floors and ceilings, shall be no less than FF

G6.3.2

The Impact Insulation Class of floors shall be no less than 55.

H1

This clause requires enclosed spaces where temperature or humidity are modified to provide adequate thermal resistance and to limit uncontrollable airflow in certain buildings.

Note

It is expected that **Karndean Opus Plank** is installed, cleaned and maintained according to instructions and best practice guides housed on the product page.

All products may be subject to fading if exposed to excessive, unfiltered UV light.

Page 2 of 3 V:230924

Product Information Declaration Karndean Opus Plank Range

Identifiers

Talpa 28125

This JPID covers all colours from Karndean Opus Plank including:

Avena 28131 Columba 28130 Argen 28129 Magna 28128 Niveus 28127 Bleached Grey Walnut 28126 Carbo 28124 Rubra 28123 Aurum 28122 Ignea 28120 Palleo 28119 Grano 28118

Sustainability

Rating System	Rating	Product Performance
Green Star Design &	Credit 12	-
As Built NZ (V1)	Credit 20	1 Point
	Credit 21	0.75 Points
Green Star	Credit 13	-
Interiors NZ (V1)	Credit 20	1 Point
	Credit 21	0.75 Points
Green Star Performance NZ (V1)	Credit 21	1 Point
Homestar V5	HC 7	1 Point
	EN 3	1.5 Points
Homestar V4	Mat-1	2 Points
	Mat-2	1 Point
Environmental Product Deceleration (EPD)		-
Embodied Carbon Emission Data		10.13kg CO2 eq

Environmental Credentials



Product Manufacturer: Karndean Country of Origin: China

Jacobsen®

Jacobsen 41D Morrin Road, St Johns, 1072 0800 800 460 jacobsen.co.nz sales@jacobsen.co.nz

NZBN: 9429040403328

Page 3 of 3

V:230924