

Juralco® Glaslide® Frameless Glass Sliding Panel System

BPIR Declaration Version 10-24v1

Designated building product Class 2

Declaration

Juralco Aluminium Building Products Ltd trading as Juralco has provided this declaration to satisfy the provisions of Schedule 1(d) of the Building (Building Product Information Requirements) Regulations 2022.

Product/system

Name	Juralco® Glaslide® Frameless Glass Sliding Panel System
Line	-
Identifier	-

Description

The Juralco Glaslide Frameless Glass Sliding Panel System is fitted with 10,12 or 15mm Toughened Glass and is available in 2,3,4 or 6-door configurations running on multiple tracks. A Magnetic latching system automatically locks all the doors in the closed position in a single movement. Glass panels max 1.1m wide and 3.0m high depending on Wind Zone, Panel height and Glass thickness. The system is especially suitable for high-end Residential, to provide a Sliding Panel Wind Protection System.

Juralco® Glaslide® Frameless Glass Sliding Panel System



BPIR Declaration

Scope of use

Glaslide® Frameless Glass Sliding Panel System

The installation manual details the documents the Juralco Glaslide Frameless Glass Sliding Panel System refers to, in relation to the New Zealand Building Code, the manufacturer's documents, products used in the System and requirements in relation to fixing and surface finishing

Glaslide Frameless Glass Sliding Panels are a permanent outdoor living system providing weather protection in a range of outdoor areas including patios, decks, extended courtyards, pool areas, cafe and bar courtyards, outdoor shopping areas etc.

Glaslide® glass doors ideal for windy locations (conform with NZS 4223.3.2016) Glass doors in 10mm, 12mm or 15mm thicknesses — maximum width and height determined by locations wind pressure.

Conditions of use

- Aluminium extrusions, components, and hardware, unless specified are manufactured to 6060 T5 specifications
- Stainless Steel components, hardware, fixings – All components to 316 grade
- The Juralco Glaslide® Frameless Glass Sliding Panel System must only be installed in accordance with the Juralco Glaslide Frameless Glass Sliding Panel System manual
- Any deviation from that specified in the Juralco Glaslide® Frameless Glass Sliding Panel System manual must only be in accordance with the site-specific PS1 with site-specific calculations and drawings listing the non-standard details
- The Juralco Glaslide® Frameless Glass Sliding Panel System must only be fabricated/installed by a Juralco approved Fabricator
- Upon completion of the installation the fabricator must supply the owner with a PS3 (Construction)

Relevant building code clauses

B1	Structure	B1.3.1, B1.3.2, B1.3.3 (c, f, h, j, m), B1.3.4
F2	Hazardous building materials	2.3.1, F2.3.3

Juralco® Glaslide® Frameless Glass Sliding Panel System



BPIR Declaration

Contributions to compliance

NZBC Compliance

The Juralco Glaslide® Frameless Glass Sliding Panel System has been reviewed by Lautrec Technology Group Ltd to demonstrate compliance with the structural requirements of the New Zealand Building Code, B1 Structure, B2 Durability (15 yrs.), F2 Hazardous material and in particular:

- AS/NZS 1170.0-2002 Structural Design Actions-Part 0: General Principals
- AS/NZS 1170.1-2002 Structural Design Actions-Part 1: Permanent, imposed, and other actions
- AS/NZS 1170.2-2021 Structural Design Actions-Part 2: Wind Actions
- AS/NZS 1664.1:1997 Aluminium structures limit state design
- NZS 3404:1997 Steel structures standard
- NZS 1720.1:2022 Timber structures Part 1, Design Method
- NZS 4223.3:2016 Glazing in buildings - Human impact and safety requirement
- NZS 4223.4:2008 Glazing in buildings - Wind, Dead, Snow and Live Actions

Note: The Juralco Glaslide Frameless Glass Sliding Panel System is NOT a barrier for Safeguard from Falling (F4), Glass Manifestation.

To be in accordance with NZS4223:3:2016

Note: NZS4223:3:2016 2.2.3 Housing: Manifestation is not required in Housing (See NZS4223:3:2016 section 3.1 for Building Type classifications). NZS4223:3:2016 2.2.4 Other Buildings: For other buildings, manifestation is required

Supporting documentation

The following additional documentation supports the above statements:

DW Glaslide Frameless Glass Sliding Panels	10-24v1	www.juralco.co.nz/assets/Uploads/Eboss/DW-Glaslide-Frameless-Glass-Sliding-Panels-10-24-v1.pdf
Producer Statement Request	10-24v1	https://ps1.juralco.co.nz/
Juralco Warranty	30 November 2024	www.juralco.co.nz/assets/Juralco-Warranty-Sheet-2022.pdf

For further information supporting Juralco® Glaslide® Frameless Glass Sliding Panel System claims refer to our website.

Juralco® Glaslide® Frameless Glass Sliding Panel System



BPIR Declaration

Contact details

Manufacture location	New Zealand
Legal and trading name of manufacturer	Juralco Aluminium Building Products Ltd trading as Juralco
Manufacturer address for service	48 Bruce McLaren Rd, Henderson, Auckland 0612
Manufacturer website	www.juralco.co.nz
Manufacturer email	specify@juralco.co.nz
Manufacturer phone number	0508 880 088
Manufacturer NZBN	9429037383664

Responsible person

As the responsible person as set out in Regulation 3, I confirm that the information supplied in this declaration is based on information supplied to the company as well as the company's own processes and is therefore, to the best of my knowledge, correct.

I can also confirm that the Juralco® Glaslide® Frameless Glass Sliding Panel System is not subject to a warning or ban under s26 of the Building Act.

Signed for and on behalf of **Juralco Aluminium Building Products Ltd trading as Juralco:**

Grant Boyce

Grant Boyce

Director

November 2024

JURALCO ALUMINIUM BUILDING PRODUCTS LTD TRADING AS JURALCO

48 Bruce McLaren Rd, Henderson, Auckland, 0612, New Zealand

09 478 8018

www.juralco.co.nz

Appendix

BPIR Ready selections

Category: Other (Custom)

B1 Structure

B1.3.1

Buildings, building elements and sitework shall have a low probability of rupturing, becoming unstable, losing equilibrium, or collapsing during *construction or alteration* and throughout their lives.

B1.3.2

Buildings, building elements and sitework shall have a low probability of causing loss of amenity through undue deformation, vibratory response, degradation, or other physical characteristics throughout their lives, or during *construction or alteration* when the *building* is in use.

B1.3.3

Account shall be taken of all physical conditions likely to affect the stability of *buildings, building elements and sitework*, including:

- (c) temperature
- (f) earthquake
- (h) wind
- (j) impact
- (m) differential movement

B1.3.4

Due allowances shall be made for:

- a. the consequences of failure,
- b. the intended use of the building,
- c. effects of uncertainties resulting from construction activities, or the sequence in which construction activities occur,
- d. variation in the properties of materials and the characteristics of the site, and
- e. accuracy limitations inherent in the methods used to predict the stability of buildings.

Juralco® Glaslide® Frameless Glass Sliding Panel System



BPIR Declaration

B2 Durability

B2.3.1

Building elements must, with only normal maintenance, continue to satisfy the performance requirements of this code for the lesser of the *specified intended life* of the *building*, if stated, or:

- the life of the building, being not less than 50 years, if: those building elements (including floors, walls, and fixings) provide structural stability to the building, or those building elements are difficult to access or replace, or failure of those building elements to comply with the building code would go undetected during both normal use and maintenance of the building

B2.3.2

Individual *building elements* which are components of a *building system* and are difficult to access or replace must either:

- all have the same durability
- be installed in a manner that permits the replacement of building elements of lesser durability without removing building elements that have greater durability and are not specifically designed for removal and replacement

D1 Access Routes

D1.3.3

Access routes shall:

- (j) Have smooth, reachable, and graspable handrails to provide support and to assist with movement along a stair or barrier
- (k) have handrails of adequate strength and rigidity as required by Clause B1 Structure

F2 Hazardous building materials

F2.3.1

The quantities of gas, liquid, radiation, or solid particles emitted by materials used in the *construction of buildings*, shall not give rise to harmful concentrations at the surface of the material where the material is exposed, or in the atmosphere of any space.

F2.3.3

Glass or other brittle materials with which people are likely to come into contact shall:

- a. if broken on impact, break in a way which is unlikely to cause injury or
- b. resist a reasonably foreseeable impact without breaking, or
- c. be protected from impact.

Juralco® Glaslide® Frameless Glass Sliding Panel System



BPIR Declaration

F4 Safety from falling

F4.3.1

Where people could fall 1 metre or more from an opening in the external envelope or floor of a *building*, or from a sudden change of level within or associated with a *building*, a barrier shall be provided.

F9 Means of restricting access to residential pools

F9.3.1

Residential pools must have or be provided with physical barriers that restrict access to the pool or the *immediate pool*

area by unsupervised young children (i.e.,

under 5 years of age). F9.3.3

A barrier surrounding a *pool* must have no permanent objects or projections on the outside that could assist children in negotiating the barrier. Any gates must

- a. open away from the pool; and
- b. not be able to be readily opened by children; and
- c. automatically return to the closed position after use.