

Juralco Louvrelite® Window Surround System

BPIR Declaration Version 11-22 v1

Designated building product Class 2

Declaration

Juralco Aluminium Building Products Ltd trading as Juralco has provided this declaration to satisfy the provisions of Schedule 1(d) of the Building (Building Product Information Requirements) Regulations 2022.

Product/system

Name	Juralco Louvrelite® Window Surround System
Line	-
Identifier	-

Description

The Juralco Louvrelite Window Surround System is designed for high-end Residential and Multi-Unit apartment blocks to provide an aesthetically pleasing and economical decorative facade solution. The Juralco Louvrelite window surround system is a decorative cladding element that is designed to be installed on top of a rainscreen cladding over a drained and ventilated cavity. It has not been designed for restraining loads or other loads other than specified in the installation manual.

Juralco Louvrelite® Window Surround System



BPIR Declaration

Scope of use

Juralco Louvrelite® Window Surround System

The Installation manual details the documents the Juralco Louvrelite Window Surround System refers to, in relation to the New Zealand Building Code, the manufacturer's documents, products used in the System and requirements in relation to fixing and surface finishing. The Juralco Louvrelite window surround system is a decorative cladding element that is designed to be installed on top of a rainscreen cladding over a drained and ventilated cavity. It has not been designed for restraining loads or other loads other than specified in the installation manual.

Conditions of use

- Only extrusions, components and hardware supplied by or specified by JABP may be used in the ® Juralco Louvrelite Window Surround System
- Aluminium extrusions, components, and hardware – unless specified are manufactured to 6060 T5 specifications
- Stainless Steel components, hardware, fixings – all components to 316 grade.
- The Juralco Louvrelite Window Surround System must only be installed in accordance with the ® Juralco Louvrelite® Window Surround System manual
- Any deviation from that specified in the Juralco Louvrelite Window Surround System manual must only be in accordance with the site-specific PS1 with site-specific calculations and drawings listing the non-standard details
- The Juralco Louvrelite Window Surround System must only be fabricated/installed by a Juralco approved fabricator

Relevant building code clauses

B1 Structure

B1.3.1, B1.3.2, B1.3.3 (c, f, h, j, m), B1.3.4

Juralco Louvrelite® Window Surround System



BPIR Declaration

Contributions to compliance

NZBC Compliance

The Juralco Louvrelite® Window Surround System has been reviewed by Lautrec Technology Group Ltd to demonstrate compliance with the structural requirements of the New Zealand Building Code

- B1 Structure,
- AS/NZS 1170.0-2002 Structural Design Actions-Part 0: General Principals
- AS/NZS 1170.1-2002 Structural Design Actions Part 1: Permanent, imposed, and other actions
- AS/NZS 1170.2-2011 Structural Design Actions-Part 2: Wind Actions.
- AS/NZS 1664.1:1997 Aluminium structures limit state design
- NZS 3404:1997 Steel structures standard
- NZS 3603:1993 Timber structures standard
- NZS3604 Wind Zones, to Very High and SED Limit up to Wind Pressure ULS = 3.0kPa

Supporting documentation

The following additional documentation supports the above statements:

DW Louvrelite Window Surround System	11-22v1	www.juralco.co.nz/assets/Uploads/resources/DW-Louvrelite-Window-Surround-System-11-22-v1.pdf
Producer Statement Request	11-22v1	https://ps1.juralco.co.nz/
Juralco Warranty	02 December 2024	www.juralco.co.nz/assets/Juralco-Warranty-Sheet-2022.pdf

For further information supporting Juralco Louvrelite® Window Surround System claims refer to our website.

Juralco Louvrelite® Window Surround System



BPIR Declaration

Contact details

Manufacture location	New Zealand
Legal and trading name of manufacturer	Juralco Aluminium Building Products Ltd trading as Juralco
Manufacturer address for service	48 Bruce McLaren Rd, Henderson, Auckland 0612
Manufacturer website	www.juralco.co.nz
Manufacturer email	specify@juralco.co.nz
Manufacturer phone number	0508 880 088
Manufacturer NZBN	9429037383664

Responsible person

As the responsible person as set out in Regulation 3, I confirm that the information supplied in this declaration is based on information supplied to the company as well as the company's own processes and is therefore, to the best of my knowledge, correct.

I can also confirm that the Juralco Louvrelite® Window Surround System is not subject to a warning on ban under s26 of the Building Act.

Signed for and on behalf of **Juralco Aluminium Building Products Ltd trading as Juralco:**

Grant Boyce

Grant Boyce

Director

December 2024

JURALCO ALUMINIUM BUILDING PRODUCTS LTD TRADING AS JURALCO

48 Bruce McLaren, Henderson, Auckland, 0612, New Zealand

09 478 8018

www.juralco.co.nz

Appendix

BPIR Ready selections

Category: Other (Custom)

Building code performance clauses

B1 Structure

B1.3.1

Buildings, building elements and sitework shall have a low probability of rupturing, becoming unstable, losing equilibrium, or collapsing during *construction or alteration* and throughout their lives.

B1.3.2

Buildings, building elements and sitework shall have a low probability of causing loss of amenity through undue deformation, vibratory response, degradation, or other physical characteristics throughout their lives, or during *construction or alteration* when the *building* is in use.

B1.3.3

Account shall be taken of all physical conditions likely to affect the stability of *buildings, building elements and sitework*, including:

- (c) temperature
- (f) earthquake
- (h) wind
- (j) impact
- (m) differential movement

B1.3.4

Due allowances shall be made for:

- a. the consequences of failure,
- b. the intended use of the building,
- c. effects of uncertainties resulting from construction activities, or the sequence in which construction activities occur,
- d. variation in the properties of materials and the characteristics of the site, and
- e. accuracy limitations inherent in the methods used to predict the stability of buildings.

B2 Durability

B2.3.1

Building elements must, with only normal maintenance, continue to satisfy the performance requirements of this code for the lesser of the *specified intended life* of the *building*, if stated, or:

- the life of the building, being not less than 50 years, if: those building elements (including floors, walls, and fixings) provide structural stability to the building, or those building elements are difficult to access or replace, or failure of those building elements to comply with the building code would go undetected during both normal use and maintenance of the building

BPIR Declaration

B2.3.2

Individual *building elements* which are components of a *building* system and are difficult to access or replace must either:

- all have the same durability
- be installed in a manner that permits the replacement of building elements of lesser durability without removing building elements that have greater durability and are not specifically designed for removal and replacement

D1 Access Routes

D1.3.3

Access routes shall:

- (j) Have smooth, reachable, and graspable handrails to provide support and to assist with movement along a stair or barrier
- (k) have handrails of adequate strength and rigidity as required by Clause B1 Structure

F2 Hazardous building materials

F2.3.1

The quantities of gas, liquid, radiation, or solid particles emitted by materials used in the *construction* of *buildings*, shall not give rise to harmful concentrations at the surface of the material where the material is exposed, or in the atmosphere of any space.

F2.3.3

Glass or other brittle materials with which people are likely to come into contact shall:

- a. if broken on impact, break in a way which is unlikely to cause injury or
- b. resist a reasonably foreseeable impact without breaking, or
- c. be protected from impact.

F4 Safety from falling

F4.3.1

Where people could fall 1 metre or more from an opening in the external envelope or floor of a *building*, or from a sudden change of level within or associated with a *building*, a barrier shall be provided.

F9 Means of restricting access to residential pools

F9.3.1

Residential pools must have or be provided with physical barriers that restrict access to the pool or the *immediate pool* area by unsupervised young children (i.e., under 5 years of age).

F9.3.3

A barrier surrounding a *pool* must have no permanent objects or projections on the outside that could assist children in negotiating the barrier. Any gates must

- a. open away from the pool; and
- b. not be able to be readily opened by children; and

Juralco Louvrelite® Window Surround System



BPIR Declaration

- c. automatically return to the closed position after use.